

UNITED STATES PATENT APPLICATION FOR:

IMPROVED TONG FOR WELLBORE OPERATIONS


INVENTORS:

**John Timothy Allen
Steven Anthony Box
Bernd Pietras
Jeffrey Michael Habetz**

ATTORNEY DOCKET NUMBER: WEAT/0142.D2

CERTIFICATION OF MAILING UNDER 37 C.F.R. 1.10

I hereby certify that this New Application and the documents referred to as enclosed therein are being deposited with the United States Postal Service on December 30, 2003, in an envelope marked as "Express Mail United States Postal Service", Mailing Label No. EV416701214US, addressed to: Mail Stop Patent Application, Commissioner For Patents, P.O. Box 1450, Alexandria, VA 22313-1450.



Signature

William B. Patterson

Name

30 Dec 2003

Date of signature

IMPROVED TONG FOR WELLBORE OPERATIONS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional of co-pending U.S. Patent Application Serial No. 10/011,049, filed December 7, 2001, which application is a divisional of U.S. Patent Application Serial No. 09/524,773, filed March 14, 2000, now Patent No. 6,412,554, which applications are herein incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

[0002] Field of the Invention

[0003] This invention is related to systems and methods for continuously circulating fluid through two tubulars as they are being connected or disconnected; and, in certain particular aspects, to continuously circulating drilling fluid through two drill pipes as they are being connected or disconnected. This invention is further related to an improved tong for connecting or disconnecting tubulars in wellbore operations.

[0004] Description of the Related Art

[0005] In many drilling operations in drilling in the earth to recover hydrocarbons, a drill string of a plurality of threadedly-interconnected pieces of drill pipe with a drill bit at the bottom is rotated to move the drill bit. Typically drilling fluid and/or "mud" is circulated to and through the drill bit to lubricate and cool the bit and to facilitate the removal of cuttings, debris, etc. from the wellbore that is being formed.

[0006] As the drill bit penetrates into the earth and the wellbore is lengthened, more joints of tubular drill pipe are added to the drill string. This involves stopping the drilling while the tubulars are added. The process is reversed when the drill string is removed, e.g. to replace the drilling bit or to perform other wellbore operations. Interruption of drilling may mean that the circulation of the mud stops

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

and has to be re-started when drilling resumes. This can be time consuming, can cause deleterious effects on the walls of the well being drilled, and can lead to formation damage and problems in maintaining an open wellbore. Also, a particular mud weight may be chosen to provide a static head relating to the ambient pressure at the top of a drill string when it is open while tubulars are being added or removed. The weighting of the mud can be very expensive.

[0007] To convey drilled cuttings away from a drill bit and up and out of a wellbore being drilled, the cuttings are maintained in suspension in the drilling fluid. If the flow of fluid with cuttings suspended in it ceases, the cuttings tend to fall within the fluid. This is inhibited by using relatively thick drilling fluid; but thicker fluids require more power to pump. Further, restarting fluid circulation following a cessation of circulation may result in the overpressuring of a formation in which the wellbore is being formed.

[0008] PCT Application PCT/GB97/02815, (John Lawrence Ayling, applicant) discloses a continuous circulation drilling method in which tubulars are added or removed from a drill string while a drill bit is rotated. In one aspect of this system, a connector is used with an inlet and an outlet for the mud, etc. The system incorporates rams to seal off and separate the flow of mud as a tubular is added or removed.

[0009] U.S. Patent 3,559,739 to Hutchinson discloses a method and apparatus for maintaining continuous circulation of foam in a well through a segmented tubing string while the tubing string is being made up or broken up. A chamber having a foam entry port is formed around the tubing string above the wellhead. A valve is provided above the foam entry port to close off the upper portion of the chamber when the tubing string is broken and the upper portion thereof raised above such valve. When it is desired to add or remove a tubing section from the tubing string, the tubing string is held by slips with its open end in the lower portion of the chamber. The upper tubing section is lifted in the chamber to above the valve. The valve is closed and foam is circulated in the chamber through the foam entry

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

port to provide for continuous foam circulation while another section of tubing is added or removed from the tubing string.

[0010] There has long been a need for an efficient and effective continuous circulation system for tubular connection and disconnections operations. There has long been a need for such a system which can operate with relatively lower viscosity drilling fluids. There has long been a need for such systems that may be used with either a top drive rig or a rotary table/kelly/kelly-bushing rig.

SUMMARY OF THE INVENTION

[0011] The present invention, in at least certain preferred embodiments, discloses a continuous circulation system for continuously circulating fluid to a tubular string while a section of tubular is being added or removed. In particular aspects, the tubular string is coiled tubing or a string of drill pipe with a drill bit at its bottom used to drill a wellbore in the earth. Circulation is maintained on such a string during joint makeup and breakout. The present invention further discloses a novel tong that isolates tubulars being handled from high pressure axial loading, thereby preventing the "launch" of a tubular from the system, and, which can be used with a standard top drive rig or with a standard kelly and rotary rig.

[0012] In one embodiment positioned between a top chamber and a bottom chamber is a gate apparatus that selectively isolates the two chambers and through which may pass the ends of two tubulars that are joined together, that are to be separated, or that are to be joined together. With suitable valving, pumps, control apparatus and devices, and flow lines, fluid flow is maintained to the tubular string beneath the system through the chambers of the system during both "breakout" and "make up" operations while undesirable leakage of fluid from the system is inhibited or prevented. Seals around each tubular - an upper tubular being added (or removed) from the string and a top tubular of the string situated beneath the upper tubular - prevent fluid from flowing out of the chambers to the environment.

PATENT

Atty. Dkt. WEAT/0142.D2
Express Mail No.: EV416701214US

[0013] In certain particular aspects the seals in the top chamber and bottom chamber are the stripper rubbers of control heads (rotating or non-rotating). In particular aspects there is an inner bushing or "sabot" that facilitates a tubular's entry into and removal from the chamber. This inner bushing or "sabot" is movably mounted in the system so that it is selectively movable with respect to the stripper rubber to facilitate entry of a tubular end into and through the stripper rubber.

[0014] In various particular embodiments the gate apparatus uses one of a variety of structures for sealingly and selectively isolating the top chamber from the bottom chamber; and for providing a selectively operable area through which tubulars may pass during continuous fluid circulation. These gate apparatuses include, in at least certain preferred embodiments, apparatus with a flapper valve, ball valve, plug valve, gate valve or with a blowout preventer (e.g. annular ram-type blind or "CSO" type).

[0015] The systems and tools of the present invention are particularly suited for underbalanced drilling operations and for extended reach drilling operations. In certain embodiments of systems and methods according to the present invention, faster connection time is achieved. In certain particular aspects in underbalanced drilling with single-phase or two-phase fluids in the wellbore, the need for check valves (or "string floats") in a drill string is reduced or eliminated; gas pockets do not need to be bled; and continuous fluid circulation can be maintained. There is no need to wait while circulation is shut off to let gas pressure in the wellbore balance with the atmosphere before a connection can be broken.

[0016] By controlling the fluid flow rate within chambers of systems according to the present invention, the threads of tubulars within the chambers are not damaged by the fluid under pressure. In certain systems according to the present invention, the chambers are movable both with respect to a system frame and with respect to a rig floor on which the system is mounted. In certain aspects this allows for heavy condensation on offshore rigs. In certain aspects an axial alignment apparatus aligns an upper tubular held by the system.

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

[0017] What follows are some of, but not all, the objects of this invention. In addition to the specific objects stated below for at least certain preferred embodiments of the invention, other objects and purposes will be readily apparent to one of skill in this art who has the benefit of this invention's teachings and disclosures. It is, therefore, an object of at least certain preferred embodiments of the present invention to provide:

[0018] New, useful, unique, efficient, nonobvious systems and methods for continuously circulating fluid through a tubular string when a tubular is being connected to or disconnected from the top of the string;

[0019] Such systems and methods useful in wellbore drilling operations, including, but not limited to, underbalanced drilling operations and extended reach drilling operations;

[0020] Such systems and methods useful with top drive rigs and rotary/kelly rigs;

[0021] Such systems and methods with inner bushings or "sabots" for facilitating tubulars' movement with respect to tubular seals or stripper rubbers;

[0022] Such systems and methods in which a variety of interchangeable gate apparatuses may be used to provide a sealed central chamber for tubular connection and disconnection;

[0023] Such systems and methods that permit operations to be conducted with relatively low viscosity drilling fluid or mud;

[0024] Such system and methods that produce wellbores with relatively greater stability due to no or lower pressure shocks to the bore by using relatively low viscosity drilling fluid, by keeping drilling fluid pressure constant and in certain aspects below formation pressure, and without the need to "break" circulation;

[0025] Such systems and methods whose use reduces the risk of stuck pipe by continuously maintaining drilled cuttings in circulation;

[0026] Such systems and methods that permit constant or almost constant drilling fluid and mud flow from the wellbore being formed to the equipment that processes the fluids;

[0027] Such systems that are closed in which the top of the drill pipe string is not open to the atmosphere; and

[0028] Such systems and methods that permit faster connection time in underbalanced drilling operations with two-phase fluids.

[0029] Certain embodiments of this invention are not limited to any particular individual feature disclosed here, but include combinations of them distinguished from the prior art in their structures and functions. Features of the invention have been broadly described so that the detailed descriptions that follow may be better understood, and in order that the contributions of this invention to the arts may be better appreciated. There are, of course, additional aspects of the invention described below and which may be included in the subject matter of the claims to this invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] A more particular description of embodiments of the invention briefly summarized above may be had by reference to the embodiments which are shown in the drawings which form a part of this Specification. These drawings illustrate certain preferred embodiments and are not to be used to improperly limit the scope of the invention which may have other equally effective or legally equivalent embodiments.

[0031] FIG. 1A is a perspective view of system according to the present invention. FIG. 1B is a cross-section view of part of the system of FIG. 1A. FIGS. 1C and 1D are side views of the system of FIG. 1A.

[0032] FIG. 2 is a cross-section view of the system of FIG. 1A.

[0033] FIG. 3 is a cross-section view of a system according to the present invention.

[0034] FIG. 4A is a perspective view of a system according to the present invention. FIG. 4B is a side view and FIG. 4C is a front view of the system of FIG. 4A.

[0035] FIG. 5 is a perspective view of a system according to the present invention.

[0036] FIG. 6 is a perspective view of a system according to the present invention.

[0037] FIG. 7 is a perspective view of a prior art kelly and kelly bushing.

[0035] FIG. 8A is a side view of a kelly bushing according to the present invention. FIG. 8B is a cross-section view along line 8B-8B of FIG. 8A.

[0036] FIG. 8C is a side view of the kelly bushing of FIG. 8A. FIG. 8D is a cross-section view along line 8D-8D of FIG. 8C of the kelly bushing as shown in FIG. 8C.

[0037] FIG. 9A is a side view of a kelly according to the present invention. FIG. 9B is a cross-section view along line 9B-9B of FIG. 9A. FIGS. 9C and 9D are cross-section views of kellys according to the present invention.

[0038] FIG. 10A is a side view of a kelly bushing according to the present invention. FIG. 10A is a view along line 10A-10A of FIG. 10B. FIG. 10B is a cross-section view along line 10B-10B of FIG. 10A. FIG. 10C is a top view of a body for the kelly of FIG. 10A.

[0039] FIG. 11 is a schematic view of a typical prior art rotary rig with which circulation systems disclosed herein according to the present invention may be used.

[0040] FIG. 12A is a side view of a prior art derrick and top drive with which

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

circulation systems according to the present invention may be used. FIG. 12B is a perspective view of the top drive of FIG. 12A.

[0041] FIG. 13A is a perspective view of a tong and motors according to the present invention. FIG. 13B is a cutaway view of the tong of FIG. 13A. FIG. 13C is an exploded view of the tong of FIG. 13A.

[0042] FIG. 14A is a perspective view of an insert according to the present invention for a tong. FIG. 14B is a side view of a tooth profile for an insert according to the present invention. FIG. 14C is a side view of inserts of a system according to the present invention.

[0043] FIGS. 15A - 15G illustrate steps in a method according to the present invention using a continuous circulation system according to the present invention.

[0044] FIG. 16A is a perspective view of a system according to the present invention. FIG. 16B is a cross-section view of the system of FIG. 16A.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0045] FIGS. 1A - 2 show a system 10 according to the present invention with a platform 12 mounted above a rotary table 13 and a platform 14 movably mounted to and above the platform 12. Two cylinders 16 are shown, each having a movable piston 18 to raise and lower the platform 14 to which other components of the system 10 are connected. Any suitable piston/cylinder may be used for each of the cylinders 16 / pistons 18 with suitable known control apparatuses, flow lines, consoles, switches, etc. so that the platform 14 is movable by an operator or automatically. Guide posts 17 (one shown in FIG. 1A) secured to the platform 12 move through tubulars 20 of the platform 14 to guide and control movement of the platform 14. Optionally, a top drive TD is used to rotate the drill string. An optional saver sub SS is interconnected between the top drive and the drill string.

[0046] A spider 22 including, but not limited to, known flush-mounted spiders, or other apparatus with selectively emplaceable slips extends beneath the platform 12

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

and accommodates typical movable slips **24** for releasably engaging and holding a tubular **26**. Tubular **26** which is the top tubular of a tubular string, e.g. a string of drill pipe, extending down from the rotary table **14** into a wellbore (not shown). The spider **22**, in one aspect, may have keyed slips, e.g. slips held with a key that is received and held in recesses in the spider body and slip so that the slips do not move or rotate with respect to the body.

[0047] The system **10** has upper control head **28** and lower control head **30**. These may be known commercially available rotating control heads. An upper tubular **32** is passable through a stripper rubber **34** of the upper control head **28** to an upper chamber **43**. Similarly, the top tubular **26** passes through a stripper rubber **36** of the lower control head **30** to a lower chamber **45**. The top tubular **26** is passable through a "sabot" or inner bushing **38**. The sabot **38** is releasably held within the upper chamber by an activation device **40**. Similarly, the top tubular **26** of the string passes through a sabot or inner bushing **42**.

[0048] Within housings **44**, **46** are, respectively, the upper chamber **43** and the lower chamber **45**. The "stripper rubbers" seal around tubulars and wipe them. The sabots or inner bushings **38**, **42** protect the stripper rubbers from damage by tubulars passing through them. The sabots also facilitate the tubular's entry into the stripper rubbers.

[0049] Movement of the sabots or inner bushing **38** with respect to the stripper rubber **34** is accomplished by the activation device **40** which, in one aspect, involves the expansion or retraction of pistons **48**, **49** of cylinders **50**, **51**. The cylinders **50**, **51** are secured to clamp parts **52**, **54**, (which are releasably clamped together) respectively, of the control heads **28**, **30**. The pistons **48**, **49** are secured, respectively, to a ring **56** to which the sabots themselves are secured. The cylinders **50**, **51** may be any known suitable cylinder/piston assembly with suitable known control apparatuses, flow lines, switches, consoles, etc. so that the sabots are selectively movable by an operator (or automatically) as desired, e.g. to expand the stripper rubbers and protect them during tubular joint passage therethrough,

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

then to remove the sabots to permit the stripper rubbers to seal against the tubulars.

[0050] Disposed between the housings **44**, **46** is a gate apparatus **60** which includes movable apparatus therein to sealingly isolate the upper chamber **43** from the lower chamber **45**. Joint connection and disconnection may be accomplished in the lower chamber or in the upper chamber.

[0051] In a particular embodiment of the system **10**, the gate apparatus **60** is a gate valve **62** with a movable gate **64** and an inner space that defines a central chamber **66** within which the connection and disconnection of tubulars can be accomplished.

[0052] In certain embodiments, the tong **70** is isolated from axial loads imposed on it by the pressure of fluid in the chamber(s). In one aspect lines, e.g. ropes or cables, or fluid operated (pneumatic or hydraulic cylinders) connect the tong to platform **14** to another aspect of a gripping device such as, but not limited to a typical rotatably mounted snubbing spider, grips the tubular below the tong and above the control head or above the tong, the snubbing spider connected to the platform **14** to take the axial load and prevent the tong **70** from being subjected to it. Alternatively the tong itself may have a jaw mechanism that can handle axial loads imposed on the tong. A power tong **70** (shown schematically in **Fig. 1A**) with a typical back-up apparatus **72**, e.g. but not limited to, a suitable known back-up tong or gripper may be used with the system **10** (and with any system according to the present invention disclosed herein). In one preferred aspect the tong uses bi-directional inserts or dies.

[0053] **FIG. 1B** illustrates one fluid power/control circuit for a system according to the present invention like the system **10**. Fluid is pumped from a fluid supply reservoir ("TANK") by a pump **74** through a line **J** and is selectively supplied to the lower chamber **45** with valves **76**, **78**, **82**, **84** closed and a valve **80** open. Fluid is selectively supplied to the upper chamber **43** with the valves **78**, **80**, **82**, **84** closed and the valve **76** open. Fluid in both chambers **43**, **45** is allowed to equalize by

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

opening valve **84** with valves **78, 82** closed. By providing fluid to at least one of the chambers **43, 45** when the chambers are isolated from each other or to both chambers when the gate apparatus is open, continuous circulation of fluid is maintained to the tubular string through the top tubular **26**. This is possible with the gate apparatus opened (when the tubulars' ends are separated or joined); with the gate apparatus closed (with flow through the lower chamber **45** into the top tubular **26**); or from the upper chamber **43** into the lower chamber when the gate apparatus is closed. A choke **75** (or other suitable flow controller) controls the rate of fluid pressure increase so that fluid at desired pressure is reached in one or both chambers and damage to the system and items therein is inhibited or prevented.

[0054] FIG. 3 shows a system **100** according to the present invention with an upper chamber **102** (defined, e.g. by a housing as is the upper chamber **43** in the system **10, FIG. 1A**) and a lower chamber **104** (defined, e.g. by a housing as is the lower chamber **45** in the system **10, FIG. 1A**). Slips **106** are like the slips **24** of the system **10** and the system **100** is usable on a rotary rig like that with the rotary table **14** of the system **10**. Upper and lower control heads **108, 110** have, respectively, stripper rubbers **112, 114**. In certain preferred embodiments the control heads are rotating control heads as are well known and commercially available.

[0055] A gate apparatus **120** separates the chambers **102, 104** and is selectively openable so that the chambers are in fluid communication. Any gate apparatus disclosed herein may be used for the gate apparatus **120**. A tong **116** is shown schematically gripping a lower end **118** of an upper tubular **122**; but it is within the scope of this invention for any embodiment for a tong to be positioned anywhere in or on the system where it can conveniently and effectively grip a tubular.

[0056] An axial alignment mechanism **124** with a tong **116** that grips the tubular has an inner throat or channel **126** for receiving the upper tubular **122**. Pistons **121**

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

of cylinders **123** are movable up and down to move the tong **116** to axially align a tubular. Known control apparatuses, flow liens, switches, consoles, etc. (wired or wireless; operator controlled and/or automatic) may be used to effect correct axial positioning of the tubulars.

[0057] A “sabot” or inner bushing **130** encircles the upper tubular **122** and facilitates movement of the upper tubular **122** with respect to a stripper rubber **112** of a control head. A top guide **132** with a wiper **134** encompasses the upper tubular **122**, guides the upper tubular through the stripper rubber **112** and protects the stripper rubber from damage by the tubular its travel with respect to the tong and the system’s chambers. A bottom guide **136** with a wiper **138** encompasses a top tubular **140** of a tubular string **142** extending into a wellbore **144**; protects the system’s chambers from damage; guides the upper tubular through the lower stripper rubber, reducing wear on it; retains the lower stripper rubber in place; and guides the tubular **140** in its travel with respect to system’s chambers.

[0058] **FIGS. 4A-4B** show a system **150** according to the present invention with support pedestals **152** on a rig floor **153** of a rig (not shown; e.g. a typical rotary table rig). The system **150** is used to either connect or disconnect an upper tubular **154** and a top tubular **156** of a string of tubulars (not shown) extending beneath the rig into a wellbore.

[0059] Components of the system **150** supported by the pedestals **152** are movable with respect to the pedestals **152** by extending or retracting pistons **158** of cylinders **160** (one shown) one on the side of each of the pedestals. At one end (bottom end) the pistons **158** are secured to the pedestals and at the other end (top end) the cylinders **160** are secured to a frame **162** that holds components of the system **150** between the pedestals **152**. Frame connections **165** move in slots (not shown) at the pedestals.

[0060] The system **150** includes a lower gripper or back-up tong **164** above which is mounted a typical blowout preventer **166**. Above the blowout preventer

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

166 is a gate apparatus **170** which may be any gate apparatus disclosed herein. A blowout preventer **168** is mounted above the gate apparatus **170**.

[0061] A tong **172** is mounted above the blowout preventer **168** for gripping and rotating the tubular **154**. In one aspect, the tong **172** is a power tong powered by tong motors **174**. This system **150** may include control heads and one or more movable sabots or inner bushings as in the system **10** above.

[0062] The tong **172** is movable with respect to the back-up tong **164** and, hence, movable with respect to the blowout preventer **168** and items below it by expanding or contracting pistons **176** of cylinders **178**. The lower end of the cylinders **168** are secured to the frame **165**.

[0063] When used in a top drive drilling system, in a system according to the present invention whatever is gripping the tubulars of the string rotates when the top drive shaft rotates.

[0064] Figs 5 and 6 illustrate alternative embodiments for upper and lower chambers and gate apparatuses for systems according to the present invention. Fig. 5 shows a system **190** according to the present invention with a housing **192** having an upper chamber **194** in which is removably positioned a lower end of an upper tubular **196** that extends through an upper stripper rubber **198**; and a lower chamber **200** in which is removably positioned a top end of a top tubular **202** (e.g. a top tubular of a string, e.g. a drill string of drill pipe) that extends through a lower stripper rubber **204**. A channel **206** between the upper chamber **194** and the lower chamber **200** is selectively openable and closable with a flapper valve **210**.

[0065] Drilling fluid is selectively pumped to the chambers **194**, **200** from a mud system **208** (any suitable known drilling fluid/mud processing system - also usable with any system disclosed herein) via lines **212**, **214** controlled by valves **216**, **218**.

Fluid is evacuated from the chambers to a reservoir **228** via lines **220**, **222** and **230** in which flow is controlled by a valve **224**. A check valve **226**, in one aspect a ball-type check valve **226** prevents backflow when circulating from the bottom

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

chamber only. The valve **210** automatically opens or closes by the action of a tubular end, e.g. by contact with the pin end of the upper tubular. To open the valve **210** pressure between the upper and lower chambers is equalized and then the pin end of the upper tubular is pulled down by moving a tong downwardly with its associated movement cylinders (not shown, like those of the system **10** or of the system **150**). The valve **210** closes automatically when a tubular's end is raised up through the channel **206**. Such automatic closing can be effected with a spring **195**, counter weight, or other apparatus or structure for supplying a closing force to the valve. The valve **224** may be set to allow fluid flow only from the upper chamber, only from the lower chamber, or to equalize fluid pressure in the two chambers.

[0066] A system **230** according to the present invention as shown in **Fig. 6** has a housing **232** that defines an upper chamber **234** and a lower chamber **236**. An upper tubular **238** has a lower end extending (removably) down into the lower chamber **236**. A top tubular **242** of a tubular string (e.g. any string disclosed herein) extends (removably) up into the lower chamber **236**. The upper tubular **238** extends through a stripper rubber **240** and the top tubular **242** extends through a stripper rubber **244**. The lower chamber **236** is sized and configured for connection and disconnection therein of the tubulars.

[0067] A gate apparatus **250**, in this case a ball or plug valve **246**, controls fluid flow between the two chambers via a channel **248**.

[0068] Any control heads, alignment mechanisms, top and bottom guides, tongs, back-ups raising and lower devices, and/or guides and wipers disclosed herein may be used with the systems of **Figs. 3, 4, 5, and 6**.

[0069] **Fig. 7** shows a prior art kelly **K** and a prior art kelly bushing **B** as are typically used with prior art rotary/kelly rigs.

[0070] **Figs. 8A and 8B** show a kelly bushing **260** according to the present invention with a plurality of spaced-apart rollers **262** each rotatably mounted on an

PATENT

Atty. Dkt. WEAT/0142.D2
Express Mail No.: EV416701214US

axle **264** which is movable up/down, in and out in a slot **266** of a support **268** on a base **270**. The rollers **262** are positioned so their outer diameters contact flat surfaces **272** of a kelly **274**. The position of the rollers **262** is adjustable by moving a leveling bar **275** up and down which raises and lowers the axles **264** in the slots **266** and slots **280**. Moving the leveling bar **275** in effect moves the intersections of the slots **266** and **280** toward and away from the apparatus center line.

[0071] Guide rods **276** guide the movement of the leveling bar **275** with respect to the base **270** and resist bending forces imposed on guide bushings **278**. The guide bushings **278** maintain the leveling bar **275** perpendicular to the guide rods and, therefore, level with respect to the base **270** so, preferably, the rollers are maintained equidistant from the center line of the device. Raising and lowering the leveling bar **275** moves the roller axles **264** and hence the rollers **262** out (**Figs. 8C, 8D**) or in (**Figs. 8A, 8B**) respectively. When the rollers move out, they allow the tool joint of the kelly to pass. When the rollers move in, they press against the flats of the kelly. This allows torque to be transmitted from the kelly bushing base to the kelly. Each of the axles **264** moves in two slots, a slot **280** in the support **282** and in a base slot **266** in the support **268**. The action of the axles **264**, slots **266** and **280**, leveling bar **275**, guide bushings **278**, and guide rods **270** maintains the rollers **262** level and equi-distant from the kelly.

[0072] **Fig. 9A** and **9b** show a kelly **290** according to the present invention with a hex-shaped portion **292** and round portion **294**. A lower end **296** of the kelly **290** is threadedly connected to an upper end of a tubular **298**, e.g. a tool joint or drill pipe. The flats of the kelly **290** have a spread that is equal to or greater than the diameter of the kelly tool joint of drill pipe tool joint. This allows the drill pipe or kelly to pass through the kelly bushing. Thus the kelly bushing remains in place when the rig lifts the kelly or drill string.

[0073] In certain aspects the kelly **290** has a diameter across the flat surfaces (i.e., from one flat surface across the cross-section of the kelly to the other) is as large or larger than the largest diameter of the tool joint **298** and others connected

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

to it, allowing the tool joints (and pipes in a drill string) to pass through a kelly bushing according to the present invention unimpeded without the need to remove the kelly bushing. **Fig. 9D** shows an alternative form **290a** of the kelly **290** of **Fig. 9A** which has a round portion **294a** corresponding to the round portion **294**, **Fig. 9A**. Edges **291** of the flat sections **292a** of the kelly **290a** are rounded off, but the flat surfaces are still of sufficient size when the diameter from one flat surface to the other is as stated above, for effective rotation of the kelly. **Fig. 9C** illustrates an alternative form for a kelly **293** which has a round portion **299** (like the round portion **294**, **Fig. 9A**) and a plurality of lobed surfaces **297** in a kelly portion **295**. In certain preferred embodiments of systems according to the present invention, the kelly is sufficiently long that part of the extension or tool joint portion of the kelly is present in the desired chamber of the system while a portion of the tool joint (rather than a hex or flats portion) is also presented to the tong. In certain preferred embodiments the body (e.g. the body **294** or the body **294a**) is sufficiently long that a part of the tool joint below the body (e.g. tool joint **298**) is within the upper chamber and part is adjacent the tong for gripping and rotating, i.e. so the tong does not grip or attempt to grip the "hex" part of the kelly and so no seal against the "hex" part is attempted. In one particular aspect the body of the new kelly is between 5 and 10 feet long; and in one aspect, about 6 feet long.

[0074] **Figs. 10A** and **10B** show a new kelly bushing **300** with a new slip bowl **312** according to the present invention for use in a typical adapter bushing **302** in a rotary **304** of a rotary rig (not shown) having a rig floor **306**.

[0075] A lip **308** of the slip bowl **312** rests on a corresponding recess **309** of the bushing **302**. A plurality of rollers **310** are rotatably mounted to a slip bowl **312** extending down into the rotary table and beneath the rig floor. Each roller **310** contacts one or more flat surfaces **313** of a kelly **314**. **Fig. 10C** shows another embodiment for the body **300** in which two halves **300a** and **300b** are selectively releasably secured together, e.g. by plates **330**, **331** and their corresponding bolts **332**, **333** extending through the plates and into one of the body halves; or by bolts (not shown) bolting the two halves together.

[0076] Using the new kelly bushing according to the present invention provides a new rotary table or rig floor with a kelly bushing below (or with a major portion below) the table or floor upper level with kelly rollers beneath the table (or floor) rather than on it. Using such a new kelly bushing also permits the use of hand slips within the slip bowl **312** associated with the new kelly bushing. The adapter bushing **302** is optional. A new kelly bushing according to the present invention of appropriate size and configuration may be provided that is emplaced in the rotary table without an adapter bushing (like the bushing, **302**).

[0077] With a circulation system according to the present invention, a longer saver sub may be used below the top drive on a top drive rig or below the hex part of a kelly on a rotary rig.

[0078] **Fig. 11** shows a typical prior art rotary rig and derrick with which a continuous circulation system according to the present invention may be used. A kelly and/or kelly bushing according to the present invention may also be used with the rig of **Fig. 11** instead of the prior art kelly and/or kelly bushing shown in **Fig. 11**. Systems according to the present invention may be used with any known prior art rotary rig.

[0079] **Figs. 12A** and **12B** show a typical prior art top drive and derrick (from U.S. Patent 4,593,773 incorporated fully herein for all purposes) with which a continuous circulation system according to the present invention (any disclosed herein) may be used. Systems according to the present invention may be used with any known prior art top drive system.

Methods For Top Drive Rigs

[0080] In certain particular methods for "breaking out" tubulars according to the present invention in which a continuous circulation system ("CC") according to the present invention (e.g. as in **Fig. 1A** or **4**) is used in a top drive drilling rig, the top drive is stopped with a joint to be broken positioned within a desired chamber of the CCS or at a position at which the CCS can be moved to correctly encompass the joint. By stopping the top drive, rotation of the drill pipe string ceases and the string

PATENT

Atty. Dkt. WEAT/0142.D2
Express Mail No.: EV416701214US

is held stationary. A spider is set to hold the string. Optionally, although the continuous circulation of drilling fluid is maintained, the rate can be reduced to the minimum necessary, e.g. the minimum necessary to suspend cuttings. If necessary, the height of the CCS with respect to the joint to be broken out is adjusted. If the CCS includes upper and lower BOP's, they are now set. One or more BOP's are optional for all systems according to the present invention.

[0081] The drain valve **82** is closed so that fluid may not drain from the chambers of the CCS and the balance valve **84** is opened to equalize pressure between the upper and lower chambers of the CCS. At this point the gate apparatus is open. The valve **76** is opened to fill the upper and lower chambers with drilling fluid. Once the chambers are filled, the valve **76** is closed and the valve **80** is opened so that the pump **74** maintains pressure in the system and fluid circulation to the drill string. The top tong and lower back-up now engage the string and the top drive and/or top tong apply torque to the upper tubular (engaged by the top tong) to break its joint with the top tubular held by the back-up) of the string. Once the joint is broken, the top drive spins out the upper tubular from the top tubular.

[0082] The upper tubular (and any other tubulars connected above it) is now lifted so that its lower end is positioned in the upper chamber. The gate is now closed, isolating the upper chamber from the lower chamber, with the top end of the top tubular of the drill string held in position in the lower chamber by the back-up (and by the slips).

[0083] The valve **78** (previously open to permit the pump to circulate fluid to a drilling swivel **DS** and from it into the drill string (as shown in **Fig. 1B**) and the balance valve **84** are now closed. The drain valve **82** is opened and fluid is drained from the upper chamber. The upper BOP's seal is released. The top tong and back-up gripper are released from their respective tubulars and the upper tubular and interconnected tubulars, a "drill stand," (e.g. a drill pipe and/or a stand of a plurality of drill pipes) is lifted with the top drive out from the upper chamber and out

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

from the upper chamber of the CCS while the pump **74** maintains fluid circulation to the drill string through the lower CCS chamber.

[0084] An elevator is attached to the drill stand and the top drive separates the drill stand from a saver sub (shown schematically in **Fig. 1A**). The separated drill stand is moved into the rig's pipe rack with any suitable known pipe movement/manipulating apparatus.

[0085] A typical breakout wrench or breakout foot typically used with a top drive is released from gripping the saver sub and is then retracted upwardly, allowing the saver sub to enter a chamber of the system. The saver sub or pup joint is now lowered by the top drive into the upper chamber of the CCS and is engaged by the top tong. The upper BOP is set.

[0086] The drain valve **82** is closed, the valve **76** is opened, and the upper chamber is pumped full of drilling fluid. Then the valve **76** is closed, the valve **78** is opened, and the balance valve **84** is opened to balance the fluid in the upper and lower chambers.

[0087] The gate is now opened and the top tong is used to guide the saver sub into the lower chamber and then the top drive is rotated to connect the saver sub to the new top tubular of the drill string (whose end is positioned and held in the lower chamber). Once the connection has been made, the top drive is stopped, the valve **80** is opened, the drain valve **82** is opened, and the upper and lower BOP's and the top tong are released. The spider is released, releasing the drill string for raising by the top drive apparatus. Then the break-out sequence described above is repeated.

[0088] In a method with the top drive and CCS used for break-out (as described above), the top drive is stopped so that rotation of the drill string ceases. The spider is set to hold the drill string. Optionally, the drilling fluid pump rate is minimized. The height of the CCS and its position with respect to a joint to be made up are adjusted if necessary. The upper and lower BOP's are set. The drain valve **82** is closed, the balance valve **84** is opened, the valve **76** is opened and

PATENT

Atty. Dkt. WEAT/0142.D2
Express Mail No.: EV416701214US

then closed (once the upper chamber is full. The valve **80** is then opened and the top tong engages the saver sub.

[0089] The top drive is activated and reversed to apply some of the torque necessary to break the connection, e.g., between 40% to 90% of the needed torque, and, in certain embodiments between 75% and 90% of the torque needed, and, in one particular aspect, about 75% of the torque needed. The top tong applies the remaining necessary torque to the saver sub. In another aspect the top tong supplies all of the needed torque. The saver sub is then spun out from a top tubular of the drill string by the top drive and lifted, by the top tong and/or top drive, into the upper chamber of the CCS.

[0090] The gate is closed to isolate the upper chamber from the lower chamber. The valve **78** is closed, the balance valve **84** is closed and the drain valve **82** is opened to evacuate the upper chamber. During these steps the pump **74** continues to pump drilling fluid to the drill string as it does throughout the process.

[0091] The BOP's and top tong and back-up are released. The saver sub is then raised out of the CCS and the top drive itself is then raised within the mast so that the next stand of drill pipe can be picked up. The new stand is then lowered into the CCS and connected to the top tubular of the drill string by rotating the new stand with the top drive. This is done by setting the tong and setting the upper BOP; closing the drain valve **82**; opening the valve **76**; filling the upper chamber with drilling fluid; closing the valve **76**; opening the valve **78**; balancing the two chambers by opening the valve **84**; applying spin-up torque with the top drive; opening the gate; lowering the lower end of the new stand into the lower chamber; connecting the lower end of the new stand to the top end of the top tubular of the drill string by rotating the top drive.

[0092] The valve **80** is then closed, the drain valve **82** is opened, the BOP's are released, the back-up is released; the spider is released; the drill string is lifted as the spider is released and drilling is resume.

Methods For Rotary Table Rigs

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

[0093] In certain methods according to the present invention using a continuous circulation system ("CCS") according to the present invention (as in **Fig. 1A**), a break-out procedure is begun by removing the kelly from the drill string and then connecting the kelly extension tool joint (with the kelly removed) to the top of the drill string to begin removal of the drill string.

[0094] The rotary is stopped and the travelling block is lifted to lift the kelly and the extension tool joint ("ETJ") into position within the CCS. The drawworks brake is set to hold the traveling block stationary and the slips of the rotary table are set to hold the drill string. Optionally, the pumping rate of the continuously circulating drilling fluid (continuously circulated by the CCS throughout this procedure) is minimized. If needed, the position of the CCS is adjusted.

[0095] The back-up is energized to engage and hold the drill string and the drain valve **82** is closed. The balance valve **84** is opened and the valve **76** is opened to fill the system's chambers with drilling fluid. Then the valve **80** is opened and the valve **76** is closed. The top tong is energized and engages the ETJ. Rotating the ETJ with the tong separates the ETJ from the drill string, freeing the drill string and apparatus etc. above it.

[0096] The kelly is then lifted away from the ETJ and raised into the upper chamber. The chambers are isolated as described above for top drive procedures and the kelly is removed from the CCS and placed to the side, e.g. in a mouse hold. The saver sub (also called "saver pup joint") is disconnected from the kelly (e.g. with manual tongs) and the saver sub (still connected to the kelly and suspended from the traveling block) is swung back over the CCS. The next joint is now lowered into the upper chamber and the top tong engages it. The chambers are filled and balanced as described above for top drive procedures and then the gate is opened and the pin end of the next joint is lowered into the lower chamber where it is then connected, by rotating the tong, to the box end of the top tubular of the drill string whose upper end is in the lower chamber. The main valve **82** is opened, the tong is released; the spider is released; and the drill string is raised

until the next tool joint (drill pipe joint) to be broken is correctly positioned in the CCS. This next joint is then broken-out as described above.

[0097] To make-up joints with the rotary table/kelly rig, the kelly is disconnected from the drill string within the CCS while the pump **74** continuously supplies drilling fluid to the drill string. The kelly is then removed from the CCS by raising the traveling block.

[0098] The saver sub is then re-connected to the kelly (e.g. using a kelly spinner and manual tongs). The kelly is then raised with the traveling block above the CCS and lowered into its upper chamber. The top tong engages the kelly and connects it to the top tubular of the drill string within the lower chamber of the CCS, all while drilling fluid is continuously provided to the drill string by the CCS.

[0099] With the kelly connected to the drill string, the rotary rotates the kelly to resume drilling.

[00100] In certain aspects when a system according to the present invention as described above is used offshore with a top drive rig, the cylinders of the frame (which is connected to the rig floor) serve the function of heave compensators. A typical heave compensation system interfaces with the cylinders (e.g. the cylinders **16**, **Fig. 1A** or **Fig. 4A**) causing the cylinders to react (the pistons move) to compensate for heaving of the rig.

[00101] **Figs. 13A - 13B** show one embodiment of a tong **170** with motors **174** (as shown in **Figs. 4A - 4C** above). As shown in **Fig. 13A**, an optional hydraulic swivel **HS** may be used with a tong **170** or, as discussed below, hydraulic fluid under pressure used by the tong may be supplied via lines within the tong itself through hoses connected to the tong. The hydraulic swivel **HS**, when used, may be located at any appropriate location, although it is shown schematically in **Fig. 13A** above the tong.

[00102] The tong motors **174** are supported by a frame **402**. It is within the scope of this invention to use any suitable motor, including, but not limited to, air

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

motors and hydraulic motors. In certain aspects the motors are low speed high torque motors without a gear box. In other aspects, as shown in **Fig. 13A**, the motors are high-speed low torque motors with associated planetary gear boxes **404** and drive gears **406**.

[00103] The tong **170** as shown in **Figs. 13A - 13C** has a gear flange **408** movably mounted on a gear wheel **409** with teeth **410** that mesh with teeth of the gears **406** for rotating the tong **170**. Rotating the gear wheel **409** rotates a housing **412** to which the gear wheel **409** is secured.

[00104] A hollow interior of the housing **412** contains three jaw assemblies **420** (two shown) each with a jaw **414** having a gripping insert or inserts **416** releasably secured to an end **417** thereof. It is within the scope of this invention to have two, three, four or more jaw assemblies **420** around the circumference of the housing **412**. It is within the scope of this invention to use any suitable known gripping inserts for the inserts **416**, including, but not limited to, inserts as disclosed in U.S. Patents 5,221,099; 5,451,084; 3,122,811 and in the references cited in each of these patents - all of which patents and references are incorporated fully herein for all purposes. The inserts **416** may be secured to and/or mounted on the jaws **414** by any known means or structure.

[00105] Each jaw **414** has an inner chamber **418** in which is movably disposed an end **422** of a piston **430**. Another end **424** of each of the pistons **430** is movably disposed in the housing **412**. The piston **430** has a central portion that sealingly extends through a channel **426** in the jaw **414**. As is described in detail below, pumping fluid into a space **425** in the chamber **418** between the piston end **422** and the jaw end **417** moves the jaw and its insert into contact with a tubular within the tong. Pumping fluid into the chamber **418** on the other side of the piston end **422**, a space **423** between the piston end **422** and an outer wall **415** of the jaws **414**, moves the jaw out of engagement with a tubular in the tong.

[00106] Fluid under pressure is provided to the chamber **418** via "flow line **435** into the space **423** and via a flow line **436** into the space **425**. Fluid is provided to

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

these lines via lines **449, 450** in the housing **412**. Of course the extent of the spaces **423, 425** changes as the piston **430** moves. Fluid is supplied to the flow lines **449, 450** via holes **437, 438** in the gear wheel **409**. There is a set of such lines (**449, 450**) and holes (**437, 438**) for each jaw assembly. The holes **437, 438** are in fluid communication with grooves **433, 434** in the gear wheel **409** and corresponding grooves **441, 442** in the gear flange **408**. Fluid is pumped through hoses **432** (e.g. in fluid communication with a typical rig hydraulic-fluid-under-pressure supply system) to channels **443, 444**, which are in fluid communication with the grooves **433, 443** and **434, 444**, respectively. This fluid is continuously supplies to the jaw assemblies through the tong. Alternatively, an apparatus is provided on or in the gear flange for selectively providing fluid under pressure to the lines **449, 450** of each jaw assembly.

[00107] The gear flange **408** is movable with respect to the gear wheel **409** so that as the gear wheel **409** and housing **412** are rotated by the motors **174**, the gear flange **408** can remain substantially stationary. A plurality of bearings **445** in grooves **446** and **447** facilitate rotation of the gear wheel **409** with respect to the gear flange **408**.

[00108] A tubular within the tong **170** extends through a channel **452** in the gear flange **408** through a channel **454** in the gear wheel **409**, through a channel **453** in the housing **412**, and in the space between the outer surfaces of the inserts **416** and a channel **455** defined by a lower inner edge of the jaws **414**.

[00109] In certain embodiments the inserts **416** of the tong **170** are "bi-directional" inserts or dies designed for handling torsion and axial loading. It is within the scope of this invention to use any suitable known inserts and/or dies for slips and/or tongs for the inserts **416**, including, but not limited to inserts as shown in U.S. Patent 5,451,084 and in the prior art cited therein. **Fig. 14A** shows an insert **460** for use as the inserts **416** which is similar to the inserts of U.S. Patent 5,451,084, incorporated fully herein for all purposes. The insert **460** has a body **461** with a plurality of recesses **462** in each of which is secured a gripper bar **464**

PATENT

Atty. Dkt. WEAT/0142.D2
Express Mail No.: EV416701214US

made, e.g., of metals such as steel, stainless steel, brass, bronze, aluminum, aluminum alloy, zinc, zinc alloy, titanium, copper alloy, nickel-based alloy, cermet, ceramic or a combination thereof, each bar with a plurality of teeth **466** for engaging a tubular in the tong **170**. In one aspect the body **461** is plastic, rubber, urethane, polyurethane or elastomeric material. **Fig. 14B** shows one particular configuration and profile for teeth **465** of a gripper bar **467** which can be used for the gripper bars **464**. **Fig. 14C** shows two inserts **416** of a jaw assembly **420** engaging a tubular **TB** (one side shown) in a tong **170** (not shown). The structure of the tong **170** as shown in **Figs. 13A - 13C** including the gear flange, the gear wheel, the bearings, and the jaw assemblies (jaws, pistons), also contributes to the tong's ability to withstand an axial force applied to a tubular held by the tong, e.g. an axial force applied to the tubular by fluid under pressure in a chamber of a circulation system according to the present invention as described herein.

[00110] **Figs. 15A - 15G** illustrate a system **500** according to the present invention and steps in a method according to the present invention. The system of **Fig. 1A** uses one set of cylinders to move the tong with respect to the upper chamber and another set of cylinders to move the frame with respect to the pedestal. In the system **500** a single cylinder/piston moves a tong **503** and an upper chamber **532** in unison, eliminating the need for a second set of cylinders.

[00111] A cylinder **511** with a movable piston **519** has a lower end mounted on a base **501**. The piston's upper end is fixed to a first plate **551** which is secured to a hollow post **552**. The upper chamber **532** is secured to a second plate **553** which is also secured to the post **552**. The tong **503** is above a third plate **554** and beneath and secured to a fourth plate **555** which is secured to the post **552**. Both plates **554** and **555** are secured to the post **552**.

[00112] The post **552** is movable up and down by the cylinder **511**/piston **519**. The post **552** is hollow and moves on a tube **502** secured to the base **501**. In one aspect the tube **502** and the post **552** are non-round to resist torsion and/or bending.

PATENT

Atty. Dkt. WEAT/0142.D2
Express Mail No.: EV416701214US

[00113] A lower chamber **531** is mounted on or secured to the first plate **551**. A spider **536** (e.g. but not limited to commercially available flush-mounted spiders) with slips **537** acts as the lower gripper or back-up. The spider **536** is mounted on a rig (not shown) as is the system shown in **Fig. 1A**. A main gate apparatus **506** acts as does the gate of the system in **Fig. 1A** and control heads **561**, **562** are like the control heads of the system of **Fig. 1A**. The movable sabot or inner bushing of the system of **Fig. 1A** may be used with the system **500**.

[00114] A kelly bushing **538** with rollers **539** facilitates movement of the kelly **509**.

[00115] As shown in **Fig. 15A** a kelly **509** is connected to a top joint **508** of a drill string. In **Fig. 15B**, the kelly **509** has been raised (e.g. by suitable means as discussed for the system of **Fig. 1A**) so that the kelly/tool joint connection is in the upper chamber **532**. The tool joint portion of the kelly **509** is gripped by the tong **503** and the upper chamber is filled with fluid while continuous fluid circulation is maintained, e.g. with a system as in **Fig. 1B**. The drill string is gripped by the slips **537** of the spider **538**. Using the tong **503**, the connection is broken in the upper chamber. As the connection is being broken and the kelly is being separated from the top joint of the drill string, the tong **503** (and kelly) is moved up by extension of the piston **519**, which also moves the upper chamber up. The piston **519**/cylinder **511** is controller and powered by the system's control system, e.g. as in the system of **Figs. 1A, 1B**. The movement of the tong and of the upper chamber moves the lower chamber **531** around the top end of the top tool joint of the drill string. The gate **506** is closed (**Fig. 15C**), the tong **503** is released and the kelly **509** is removed from the upper chamber **532** (**Fig. 15D**). Fluid circulation to the drill string is maintained during all these steps as in the system of **Fig. 1A**.

[00116] As shown in **Fig. 15E**, the lower end of a new tool joint **570** (connected to the kelly - not shown in **Fig. 15E**) has been introduced through the tong **503** into the upper chamber **532**. The gate **506** is opened. The piston **519** is retracted lowering the tong **503** and the upper chamber **532** so that the top end of the drill string enters the upper chamber **532**. The tong **503** grips the tool joint **570** (**Fig.**

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

15G) and makes-up the connection. Fluid is continuously circulated to the drill string throughout the method as in the system of **Fig. 1A**.

[00117] **Figs. 16A** and **16B** show a system **600**, like the system of **Fig. 4A**, but with the side cylinders **160** deleted. The system **600** has a new kelly bushing **602** (like the kelly bushing of **Fig. 10A**). A pedestal **604** is mountable on a track on a rig (not shown) e.g. as a prior art "Iron Roughneck" is mounted on a track on a rig.

[00118] As shown in **Fig. 16A** a system module **SM** may be releasably secured to a lower portion **LP** of the pedestal **604** so that the module **SM** is selectively removable from and emplaceable on the pedestal lower portion. A single set of selectively operable cylinders **606** is mounted to a frame **608** for moving the system portion **SP**. Upper chamber **632**, lower chamber **631** and tong **603** (like the tong **172**, **Fig. 4A**) are interconnected by plates **621**, **622**, **625** and members **623**, **624**. A back-up gripper **610** is like the back-up **72** of **Fig. 1A**. The chambers **632**, **631** are like the upper and lower chambers of previously-described systems herein with the same sabots, control heads, sealing apparatus and control system. A kelly bushing **630** is like that of **Fig. 10A**. A gate apparatus **636** is like that of previously-described systems.

[00119] The present invention, therefore, provides in some, but not necessarily all, embodiments a system for continuously circulating fluid to and through a hollow tubular string while an upper hollow tubular is added to or removed from a top of the tubular string, the system including chamber apparatus with a bottom opening, a top opening and sealing apparatus for sealingly encompassing a portion of the top of the tubular string, the chamber apparatus sized for accommodating connection and disconnection therein of the upper hollow tubular to the top of the tubular string, apparatus for isolating the upper hollow tubular with a portion in the chamber apparatus from fluid pressure loading within the chamber apparatus. Such a method may have one or some (in any possible combination) of the following: gate apparatus; wherein the hollow tubular string is coiled tubing; wherein the hollow tubular string is made up of a plurality of hollow tubulars

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

connected end-to-end each having a top-to-bottom fluid flow channel therethrough; and/or wherein the hollow tubular string is a drill string.

[00120] The present invention, therefore, provides in some, but not necessarily all, embodiments a tong for use in wellbore operations, the tong having a housing with a hollow interior, a gear wheel secured to the housing for rotation therewith, the gear wheel having a toothed outer circumference for mating with teeth of a drive shaft of a driving motor, a gear flange mounted on top of the gear wheel so that rotation of the gear wheel does not rotate the gear flange, and a plurality of spaced-apart jaw assemblies within the housing's hollow interior, each jaw assembly having a jaw for selectively engaging a portion of a tubular to be gripped and rotated by the tong. Such a tong may have one or some (in any possible combination) of the following: fluid flow apparatus for selectively conveying operating fluid under pressure through the tong to the jaw assemblies for selectively operating the jaw assemblies; wherein the plurality of spaced-apart jaw assemblies is three spaced-apart jaw assemblies; wherein each jaw assembly of the plurality of jaw assemblies has at least one insert thereon for engaging the tubular; wherein the inserts are toothed inserts; wherein the inserts are configured for resisting both axial and radial loading; wherein each jaw assembly has a jaw body with an inner chamber having an outer wall with a channel therethrough, a piston with a first end in the inner chamber, the first end secured to or formed of an intermediate portion movable in the channel of the outer wall of the inner chamber, and a first end, and a second end secured to or formed of the intermediate portion, the second within the housing of the tong, and the jaw body selectively movable with respect to the piston into and out of engagement with the tubular by selectively applying fluid under pressure on one side of the first end of the piston; a plurality of bearings between the gear flange and the gear wheel for facilitating movement of the gear wheel with respect to the gear flange; and/or wherein the tong's gear flange, gear wheel, jaw assemblies and bearings are configured and sized to resist axial loading on the tong.

PATENT

Atty. Dkt. WEAT/0142.D2

Express Mail No.: EV416701214US

[00121] The present invention, therefore, provides in some, but not necessarily all, embodiments a tong for use in wellbore operations, the tong having a housing with a hollow interior, a plurality of jaw assemblies movably mounted in the hollow interior of the housing, gear structure on the housing for mating co-action with a tong drive apparatus, and internal fluid flow apparatus for conducting fluid under pressure through the tong to the jaw assemblies for selectively operation of the jaw assemblies for engaging and disengaging from a tubular to be gripped and rotated by the tong.

[00122] In conclusion, therefore, it is seen that the present invention and the embodiments disclosed herein and those covered by the appended claims are well adapted to carry out the objectives and obtain the ends set forth. Certain changes can be made in the subject matter without departing from the spirit and the scope of this invention. It is realized that changes are possible within the scope of this invention and it is further intended that each element or step recited in any of the following claims is to be understood as referring to all equivalent elements or steps.